



R E S I D E N T I A L O V E R H E A D D O O R S



RESIDENTIAL Buyer's Guide

PLEASE VISIT OUR WEBSITE AT WWW.CHIOHD.COM TO SEE OUR ENTIRE LINE OF SECTIONAL AND ROLLING STEEL DOORS.

ASK YOUR DOOR PROFESSIONAL AT:

C.H.I. Overhead Doors are manufactured in Arthur, Illinois, USA.



THE DOOR TO QUALITY.

C.H.I. Overhead Doors
1485 Sunrise Drive
Arthur, Illinois 61911
www.chiohd.com

Catalog Number RES-BG0905R13
© 2013 C.H.I. Overhead Doors 11.09





Few doors in your home get more use than your garage door - it truly is the largest moving object in your house. More than any other door, it needs to work dependably and stand up to the elements for years on end. Built to meet these challenges – and look good doing it – C.H.I. Overhead Doors gives you a wide range of options that fit your home's individuality and help you maintain your investment in it.



STRONG. BEAUTIFUL.

Made with only the finest materials and built by some of the most skilled craftsmen in the business, all of our residential doors are designed with precision to add beauty and value to your home.



Pictured. 8' x 8' and 16' x 8' 2294 sandstone doors with optional plain windows

TOUGH. DEPENDABLE. STYLISH.





HIGH-DEFINITION MOLDED FIBERGLASS DOORS

Your home reflects who you are and allows you to make the statement you choose. As the largest door on your home, your garage door provides a unique opportunity to showcase your style. C.H.I. has a sophisticated line of doors for homes that require more than the standard look. Not only does the 2700 series boast an intriguing appearance, but it's also energy-efficient with a thermally-broken polyurethane core, providing a superior insulation rating and optimum protection from the outside elements. Created for those who choose to create a statement.


Pictured. 2, 9' x 8' 2702 almond doors



8' x 7' 2752 oak woodtone with arched long monticello windows with brass caming.

2700 SERIES Polyurethane Insulation

- Sections are 2" thick with a formed fiberglass face and a 25-gauge flush steel interior skin that is factory-finished in white
- Exterior skins are factory-finished in six designer colors: white, almond, evergreen, mahogany, walnut and oak with optional wood-tone available in oak, mahogany and walnut
- Unfinished² (tan) exterior skins are available for field gel staining
- Optional 1/2" insulated designer lites are available with a beveled acrylic face and 1/8" DSB obscure glass back with brass or platinum caming
- Optional Endurance and Appearance Package³ upgrades available
- Concealed steel plates run continuously from top to bottom of each section for fastening hardware
- Bottom weather seal utilizes an aluminum retainer and extruded virgin vinyl
- Available widths for all models: 8', 9', 10', 12', 16' and 18'
- All models available heights: 7' to 14' in 3" height increments (except 8'3", 8'6" and 10'3")
- R-value¹ for all models - 16.95



2701-02-03-51-52 DOOR CONSTRUCTION

The sections are 2" thick with a CFC[®] free polyurethane injected core between a formed fiberglass face and a 25-gauge flush steel interior skin that is thermally-broken for optimum weather protection.



FEATURES

REFINED. INTRIGUING.

For additional information, please see numbered footnotes on page 30.



FIBERGLASS FACED CARRIAGE HOUSE DOORS

The carriage house style door has never looked better. The 5500 and 5800 Series doors from C.H.I. Overhead Doors combine the classic look of wood with the rugged durability of fiberglass. These doors feature a lightweight, impact resistant fiberglass exterior that is virtually maintenance-free. Factory finished in three designer colors, and adhered to a steel base section that is both resilient and energy-efficient, this door will accent your home with an elegant look while providing the durable qualities you desire.


Pictured. 9' x 8' 5531A sandstone door with optional arched stockton windows and plain glass
16' x 8' 5531A sandstone door with optional 2-2pc arched stockton windows and plain glass

These models are also available in




5500 SERIES Polystyrene Insulated

5800 SERIES Polyurethane Insulated



8' x 7' 5815 white with optional madison windows and wrought iron hardware.



- The impact-resistant fiberglass bead-board and Poly accent battens are laminated to the steel sections with high performance adhesives. The sections are then factory finished in white, almond or sandstone
- Glazing options include plain, tinted, obscure, glue chip or seeded; available in the top two sections of door
- Faux windows are an option with the background color always being black and can be combined with all window section options
- **Series 5500** are 2" thick CFC[®] free polystyrene insulated base sections
- **Series 5800** are 2" thick CFC[®] free polyurethane insulated thermally-broken base sections
- 2-7/16" total section thickness
- Wood-grained steel interior, pre-finished in white
- One set of spade decorative hardware is standard for all doors. Optional Barcelona or Wrought Iron designs replicate an old-world look
- Optional Appearance Package⁴ upgrade available
- R-value for the **5500 Series** - 10.67
R-value⁴ for the **5800 Series** - 17.92



5500



5800

DOOR CONSTRUCTION

5500 Series. Utilizes a steel base sandwich section with a CFC[®] free polystyrene core. **5800 Series.** Utilizes a CFC[®] free polyurethane injected steel thermally-broken base section.

FEATURES

For additional information, please see numbered footnotes on page 30.



WOOD FACED CARRIAGE HOUSE DOORS


Classic style delivered in a bold, modern way. C.H.I. Overhead Doors has always been one step ahead of the curve with the 5400 Series. The 5400 and 5700 Series take another step forward – utilizing Western Red Cedar or Fijian Mahogany boards to create a dynamic, yet timeless look that is backed by a rigid steel base section. Top it all off with a field stain and the decorative hardware and window options of your choice to create a door that truly says...welcome home.

Pictured. 16' x 7' 5732 cedar field stained with optional madison windows and seeded glass

These models are also available in



8' x 7' 5435A mahogany unfinished with optional arched madison windows.



5400 SERIES Polystyrene Insulated

5700 SERIES Polyurethane Insulated

- The wide tongue-and-groove cedar boards and smooth cedar or mahogany accent battens are laminated to the steel base sections with high performance adhesives. The door face is manufactured unfinished² for field painting or staining.
- Glazing options include plain, tinted, obscure, glue chip or seeded; available in the top two sections of door
- Faux windows are an option with the background color always being black and can be combined with all window section options
- **Series 5400** are 2" thick CFC[®] free polystyrene insulated base sections
- **Series 5700** are 2" thick CFC[®] free polyurethane insulated thermally-broken base sections
- 2-3/4" total section thickness
- Wood-grained steel interior, pre-finished in white
- One set of spade decorative hardware is standard for all doors. Optional Barcelona or Wrought Iron designs replicate an old-world look
- Optional Appearance Package¹ upgrade available
- R-value for the **5400 Series** - 10.78
R-value¹ for the **5700 Series** - 18.03



5400



5700

DOOR CONSTRUCTION

5400 Series. Utilizes a steel base sandwich section with a CFC[®] free polystyrene core. **5700 Series.** Utilizes a CFC[®] free polyurethane injected steel thermally-broken base section.

FEATURES

For additional information, please see numbered footnotes on page 30.



PRE-FINISHED STEEL CARRIAGE HOUSE DOORS


True carriage house style doesn't have to be complex. A durable, maintenance-free steel exterior, overlaid with poly accent battens creates the timeless look of the 5300 and 5600 Series from C.H.I. Overhead Doors. A durable steel base section provides the foundation for an addition to your home that will last for years to come. This door just helps to prove that sometimes the best things in life are simple.

Pictured. 3, 9' x 7' 5334A sandstone doors with optional arched stockton windows and optional wrought iron hardware

These models are also available in



8' x 7' 5331A white overlays and sandstone sections, optional faux windows with spade hardware.



5300 SERIES Polystyrene Insulated

5600 SERIES Polyurethane Insulated

- Accent battens are laminated to the steel sections with high performance adhesives. The sections are then factory finished in white, almond, or sandstone. Almond or sandstone doors are also available with white accent battens for a two-tone design.
- Glazing options include plain, tinted, obscure, glue chip or seeded; available in the top two sections of door
- Faux windows are an option with the background color always being black and can be combined with all window section options
- **Series 5300** are 2" thick CFC[®] free polystyrene insulated base sections
- **Series 5600** are 2" thick CFC[®] free polyurethane insulated thermally-broken base sections
- 2-7/16" total section thickness
- Wood-grained steel interior, pre-finished in white
- One set of spade decorative hardware is standard for all doors. Optional Barcelona or Wrought Iron designs replicate an old-world look
- Optional Appearance Package¹ upgrade available
- R-value for the **5300 Series** - 10.29
R-value¹ for the **5600 Series** - 17.54



5300



5600

FEATURES

DOOR CONSTRUCTION

5300 Series. Utilizes a steel base sandwich section with a CFC[®] free polystyrene core. **5600 Series.** Utilizes a CFC[®] free polyurethane injected steel thermally-broken base section.

For additional information, please see numbered footnotes on page 30.



ALL-STEEL SANDWICH TYPE CARRIAGE HOUSE COLLECTION


For beauty and durability, the 5216 and 5283 Carriage House sandwich doors from C.H.I. are a great choice. Both models replicate the look of a traditional carriage house door while increasing structural rigidity and R-value by encasing insulation between two steel skins. This allows you, the homeowner, to combine energy savings with the elegance of the old-world craftsmanship. Multiple color, hardware and window options provide a custom look that adds value and curb appeal for years to come.

Pictured. 16' x 7' 5216 white with optional cascade windows and spade hardware

These models are also available in




- MODEL 5283** Short Stamp, Insulated Polystyrene
- MODEL 5983** Long Stamp, Insulated Polystyrene
- MODEL 5216** Short Stamp, Insulated Polyurethane
- MODEL 5916** Long Stamp, Insulated Polyurethane



9' x 7' 5916 mahogany Accents woodtone with optional newport lites and barcelona 2 exterior hardware.

- **Models 5283/5983** 2" door sections are formed from 27-gauge exterior and 27-gauge interior galvanized draw quality steel
- **Models 5216/5916** 2" exterior sections are formed from 26-gauge
- Optional Appearance Package¹ upgrade available for **Models 5283/5983**
- Optional Endurance and Appearance Package¹ upgrades available for **Models 5216/5916**
- One set of Spade decorative hardware is standard for all doors. Optional Barcelona or Wrought Iron designs replicate an old-world look
- Glazing options include plain, tinted, obscure, glue chip, seeded, newport, hampton, lasalle and florence with five optional insert designs
- Colors² available in **Models 5283/5983** are white, almond or sandstone; **Models 5216/5916** are white, almond, sandstone or brown
- Accents wood tones available in cedar, mahogany, dark oak and light oak
- R-value³ for the **Models 5283/5983** - 9.65
R-value³ for the **Models 5216/5916** - 16.55



DOOR CONSTRUCTION


(A) 5283/5983 utilizes a 1-13/18" CFC[®] free polystyrene insulation glued on both sides between 27-ga. exterior and 27-ga. interior skins, (B) 5216/5916 employs a high-density CFC[®] free polyurethane injected core with a 26-ga. exterior and 27-ga. interior skins and is thermally-broken for added weather protection.

FEATURES

ELEGANT. DURABLE.



For additional information, please see numbered footnotes on page 30.



8' x 7' 5251 almond with optional arched madison inserts and barcelona 1 exterior hardware.

MODEL 5250	Short Stamp, Uninsulated
MODEL 5251	Short Stamp, Insulated
MODEL 5950	Long Stamp, Uninsulated
MODEL 5951	Long Stamp, Insulated

25-GAUGE ALL-STEEL PAN TYPE CARRIAGE HOUSE COLLECTION

While maintaining the elegant appearance of our premier models, these all-steel Carriage House doors perfectly combine the beauty and charm of a traditional wood carriage house door with the durability and value of a pan-style door. The 5250/5950 models are deeply embossed with a wood grain finish, available in a variety of colors, and have several window options to choose from. Decorative handles and hinges are standard, and can be upgraded to wrought iron for a truly old-world look that will complement your home perfectly.

5251/5951 DOOR CONSTRUCTION

These models utilize 25-gauge exterior steel skin with 1-3/8" thick CFC¹⁰ free polystyrene foam insulation with a vinyl back cover. Steel end and intermediate stiles are held firmly in place by a tab-loc system, creating increased strength and rigidity.



FEATURES

CHARMING. PRACTICAL.

Pictured. 16' x 7' 5951 white door with optional 4 pc arched stockton windows and wrought iron hardware

These models are also available in





HIGH-DEFINITION RECESSED PANEL

They may look like wood, but these models are actually all-metal, maintenance-free insulated doors. The front and back skins are made with a pre-finished, wood grain embossed steel and the core is filled with high density CFC¹⁰ free polyurethane for optimum weather protection. An all-metal exterior is used on both the panels as well as the overlays to ensure years of worry free maintenance.

Pictured. 9' x 7' 2294 white with optional stockton window designs
16' x 7' 2294 white with optional stockton window designs




8' x 7' 2296 sandstone with optional plain glass

DISTINCT. CLASSIC.




- MODEL 2298** Short Panel, Insulated
- MODEL 2296** Combination Panel, Insulated
- MODEL 2294** Long Panel, Insulated


- 2" thick door exterior sections are formed from 25-gauge galvanized draw quality steel and the interior is 27-gauge steel
- Aluminum wood grain embossed overlays come pre-finished the same color as the door and are mechanically and chemically fastened to the door
- Colors² available in your choice of white, almond or sandstone
- Glazing options include plain, tinted and glue chip
- Optional window designs in prairie, stockton, madison and sunburst
- Custom coated designed springs for smooth operation and easy lifting
- High-density CFC¹⁰ free polyurethane injected core
- Section joints are roll-formed into a tongue-and-groove design which produces a superior weather seal
- Optional Endurance and Appearance Package⁴ upgrades available
- Bottom weather seal utilizes an aluminum retainer and extruded virgin vinyl
- Long-lasting durable rollers assure consistent, efficient operation
- R-value¹ for the **Models 2294/96/98** - 12.35



2294




2296



2298

DOOR CONSTRUCTION

These models utilize 25-gauge exterior and 27-gauge interior steel skins. Filled with foamed-in-place CFC¹⁰ free polyurethane to better safeguard against the elements and add structural rigidity to an already durable model.



For additional information, please see numbered footnotes on page 30.


FEATURES



ALUMINUM FULL-VIEW DOOR

A dramatic statement, made to fit your contemporary residential application. The 3295 Series full-view door from C.H.I. perfectly blends the raw industrial look of aluminum with a clean architectural design. The aluminum can be powder-coated nearly any color, with several glazing options, to create the perfect door to accent your home.

Pictured. 16' x 7' 3295 powdercoated dark bronze with optional tinted windows



8' x 7' 3295 anodized aluminum with 1/8" plain glass and optional aluminum panels in bottom section

MODEL 3295 Aluminum Full-View Door

- Stylish 2" aluminum stiles with a tongue-and-groove rail frame construction provides a superior joint strength
- 4" top and bottom rail and 2" intermediate rails create additional perimeter strength
- Extrusions feature a closed construction for a rigid frame
- Available in clear anodized or white - optional powdercoating available in a multitude of colors
- Hidden through-bolt assembly insures maximum structural integrity
- Optional aluminum panels may be specified to create solid sections and are available as insulated or non-insulated
- Glazing options are 1/8" plain, tinted or frosted (DSB), 1/8" (polycarbonate), 1/4" (tempered) or 1/2" (insulated, tempered) glass
- 1/8" plain glass is standard
- Each full-view section utilizes white and gray retainers and are painted to match all powdercoated doors
- Heavy-duty 14 gauge hinges offer stability and longer life
- Long-lasting 10 ball rollers assure consistent, efficient operation
- Bottom U-shaped astragal is standard

DOOR CONSTRUCTION

This model features closed-constructed aluminum extrusions, assembled with hidden through-bolts for maximum structural rigidity.



FEATURES

RESILIENT. STURDY.

For additional information, please see numbered footnotes on page 30.



THERMALLY-BROKEN, POLYURETHANE CORE SANDWICH DOOR

This exceptional line of garage doors incorporates a thermally-broken section design for superior weather protection. A 26-gauge exterior steel skin and 27-gauge interior steel skin filled with foamed-in-place polyurethane creates an extremely rigid barrier. A continuous section joint seal that impedes air infiltration additionally enhances this door. Available in six designer colors and a diverse collection of window options, this door will add value and appeal to your home for years to come.

Pictured. 16' x 8' 2216 white with optional 2-4 pc sunburst windows
9' x 8' 2216 white with optional 4 pc sunburst windows

These models are also available in



8' x 7' 4216 bronze with optional cascade window inserts.

SUPERIOR. THERMALLY-BROKEN.

- MODEL 2216** Short Panel, Urethane Insulated
- MODEL 2217** Flush, Urethane Insulated
- MODEL 4216** Long Panel, Urethane Insulated

- Door exterior sections are formed from 26-gauge galvanized draw quality steel and the interior is 27-gauge steel
- High-density CFC[®] free polyurethane injected core
- Long-lasting durable rollers assure consistent, efficient operation
- Heavy-duty 14-gauge hinges with "wide body" pattern for greater stability and longer life
- Colors³ available in your choice of white, almond, sandstone, brown, bronze, or evergreen
- Concealed steel plates run continuously from top to bottom of each section for fastening hardware
- Optional Endurance and Appearance Package⁴ upgrades available
- Glazing options include plain, tinted, obscure, hawthorne, somerset, newport, hampton, temple and florence with a variety of optional insert designs
- Thermally-broken for optimum weather protection
- Bottom weather seal utilizes an aluminum retainer and extruded virgin vinyl
- A continuous weather seal at the section joint assures maximum protection from the elements
- R-value¹ for the **Models 2216/4216** - 17.19
R-value¹ for the **Model 2217** - 17.54

DOOR CONSTRUCTION

These models utilize 26-gauge exterior and 27-gauge interior steel skins injected with CFC[®] free polyurethane insulation. The thermally-broken tongue-and-groove section joint includes a continuous weather seal offering exceptional protection from the elements.



FEATURES

For additional information, please see numbered footnotes on page 30.



1485

RAISED PANEL/FLUSH SANDWICH DOOR

An attractive, select model engineered for durability and energy efficiency. These models are available in 7 pre-painted, easy to care for colors, with an insulated core that protects through the harshest conditions. The beauty of this door is continued on the inside with polyester coated steel protection. Designed to complement a wide variety of home styles, this model will provide many years of dependable service.

Pictured. 3, 9' x 8' 2283 white doors with optional plain glass

These models are also available in



8' x 7' 2284 gray with optional hampton designer lites.

STRONG. STYLISH.

- MODEL 2283** Raised Panel, Insulated
- MODEL 2284** Flush Panel, Insulated
- MODEL 4283** Long Panel, Insulated

- Door sections are formed from 27-gauge galvanized draw quality steel
- Section joints are roll-formed into a tongue-and-groove design which produces a superior weather seal
- Long-lasting rollers assure consistent, efficient operation
- Bottom weather seal utilizes an aluminum retainer and extruded virgin vinyl
- Concealed steel plates run continuously from top to bottom of each section for fastening hardware
- Extension or torsion springs are coated and individually computer-calibrated to lift your door
- Colors² available in your choice of white, almond, sandstone, brown, bronze, gray, or evergreen
- Glazing options include plain, tinted, obscure, hawthorne, somerset, newport, hampton, temple and florence with a variety of optional insert designs
- Optional Appearance Package¹ upgrade available
- Hinges are stamped from galvanized steel in a "wide body" pattern for greater stability and longer life
- Optional automatic latching lock system opens easily from inside or outside
- Double sided steel doors are 2" thick
- R-value for the **Models 2283/4283** - 9.65
R-value for the **Model 2284** - 10.29

DOOR CONSTRUCTION

These models utilize 27-gauge exterior and 27-gauge interior steel skins. CFC[®] free polystyrene insulation is secured in place with a urethane adhesive to increase structural integrity. The front and back skins are locked together in a tongue-and-groove design for years of worry-free protection.



FEATURES

For additional information, please see numbered footnotes on page 30.



24-GAUGE RAISED PANEL STEEL

For a traditional-looking, heavy-duty steel door, the 2240-41 and 4240-41 models are truly among the best around. Available in five designer colors, it is an attractive top-of-the-line door that will both complement the looks of your home and provide dependable protection for many years. Designed to accompany a wide variety of home styles, this heavy-gauge model is fit for a long life.

8' x 7' 4240 evergreen with optional mission window inserts.



MODEL 2240	Short Panel, Uninsulated
MODEL 2241	Short Panel, Insulated
MODEL 4240	Long Panel, Uninsulated
MODEL 4241	Long Panel, Insulated

- Door sections are formed from heavy, 24-gauge galvanized draw quality steel
- Section joints are roll-formed into a tongue-and-groove design which produces a superior weather seal
- Bottom weather seal utilizes an aluminum retainer and extruded virgin vinyl
- Long-lasting rollers assure consistent, quiet and efficient operation
- Inside stiles are made of galvanized steel and stile holes are "dimpled" for increased holding power
- Extension or torsion springs are coated and individually computer-calibrated to lift your door
- Colors³ available in your choice of white, almond, sandstone, brown, or evergreen
- Glazing options include plain, tinted, obscure, hawthorne and somerset with a variety of optional insert designs
- Hinges are stamped from galvanized steel in a "wide body" pattern for greater stability and longer life
- Optional automatic latching lock system opens easily from inside or outside
- **Models 2241/4241** include 1-3/8" CFC¹⁰ free polystyrene insulation with a vinyl back cover
- R-value for the **Models 2241/4241** - 7.94

2241/4241 DOOR CONSTRUCTION

These models utilize 24-gauge exterior steel skin with 1-3/8" thick CFC¹⁰ free polystyrene foam insulation with a vinyl back cover. Steel end and intermediate stiles are held firmly in place by a tab-loc system, creating increased strength and rigidity.



FEATURES

BEAUTIFUL. DEPENDABLE.



Pictured. 18' x 8' 2241 white with optional stockton windows

These models are also available in





25-GAUGE RAISED PANEL STEEL

Built for both longevity and value, this door recreates the elegant look of wood with a deeply-embossed, distinctive panel design. It has the appearance of our top-of-the-line models, yet remains economical and efficient – making it one of our most popular models. Available in four designer colors, this durable steel door complements the look of almost any home.

Pictured. 16' x 8' 2251 sandstone door with optional stockton windows
9' x 8' 2251 sandstone with optional stockton windows

These models are also available in




8' x 7' 2255 white with optional cathedral window inserts.

QUIET. ENERGY-EFFICIENT.

MODEL 2250	Short Panel, Uninsulated
MODEL 2251	Short Panel, Insulated
MODEL 2255	Short Panel, Insulated
MODEL 4250	Long Panel, Uninsulated
MODEL 4251	Long Panel, Insulated
MODEL 4255	Long Panel, Insulated

- Door sections are formed from heavy, 25-gauge galvanized draw quality steel
- Section joints are roll-formed into a tongue-and-groove design which produces a superior weather seal
- Inside stiles are made of galvanized steel and stile holes are “dimpled” for increased holding power
- Bottom weather seal utilizes an aluminum retainer and extruded virgin vinyl
- Colors³ available in your choice of white, almond, sandstone, brown or desert tan
- Glazing options include plain, tinted, obscure, hawthorne and somerset with a variety of optional insert designs
- **Models 2251/4251** include 1-3/8” CFC¹⁰ free polystyrene insulation with a vinyl back cover
- **Models 2255/4255** include 9/16” CFC¹⁰ free polystyrene insulation with a vinyl back cover
- R-value for the **Models 2251/4251** - 7.94
R-value for the **Models 2255/4255** - 3.56



DOOR CONSTRUCTION

(A) 2251/4251 utilize a 1-3/8” thick CFC¹⁰ free polystyrene insulation, while models (B) 2255/4255 employ a 9/16” thick CFC¹⁰ free polystyrene insulation with vinyl back cover. Each model utilizes a 25-gauge exterior steel skin. Steel end and intermediate stiles are held firmly in place by a tab-loc system, creating increased strength and rigidity.

For additional information, please see numbered footnotes on page 30.

FEATURES

STANDARD WINDOW DESIGN TRIMS.

C.H.I. offers numerous insert designs that add distinction to any home. The convenient interchangeable inserts allow you to transform the look of your door instantly by simply switching insert patterns. Inserts are U.V. protected and are available in all door colors. The inserts can also be painted to match existing trim colors on your home.

SHORT PANEL

2240-41 / 2250-51-55 / 2283-84 / 2216-17 Series



2-4 Piece Sunburst



8 Piece Sunburst



7 Piece Sunburst



6 Piece Sunburst



5 Piece Sunburst




Cathedral




Sherwood




Stockton



Cascade



Mission



Waterton

LONG PANEL


4240-41 / 4250-51-55 / 4283 / 4216 Series



2-2 Piece Sunburst



4 Piece Sunburst



3 Piece Sunburst



Sherwood



Cascade




Stockton




2-2 Piece Arched Stockton




4 Piece Arched Stockton




Madison




2-2 Piece Arched Madison



4 Piece Arched Madison




Mission



Waterton

RECESSED LONG*

2294 Series



Prairie



Stockton



Madison



Sunburst

RECESSED COMBO*

2296 Series



Prairie




Stockton



Madison

RECESSED SHORT*

2298 Series



Prairie



Stockton



Madison




Sunburst

ALL-METAL SHORT PANEL


5250-51 / 5283 / 5216 Series




Cascade




Stockton




2-2 Piece Arched Stockton




3 Piece Arched Stockton




4 Piece Arched Stockton




Madison



2-2 Piece Arched Madison




3 Piece Arched Madison




4 Piece Arched Madison

ALL-METAL LONG PANEL


5950-51 / 5983 / 5916 Series




Cascade



Stockton




2-2 Piece Arched Stockton



3 Piece Arched Stockton




4 Piece Arched Stockton




Madison



2-2 Piece Arched Madison



3 Piece Arched Madison



4 Piece Arched Madison

SANDWICH OVERLAY SINGLE


5300 / 5400 / 5500 / 5600 / 5700 / 5800 Series



Stockton



2-2 Piece Arched Stockton



4 Piece Arched Stockton



Madison




2-2 Piece Arched Madison



4 Piece Arched Madison

SANDWICH OVERLAY DOUBLE


5300 / 5400 / 5500 / 5600 / 5700 / 5800 Series



Stockton



2-2 Piece Arched Stockton



4 Piece Arched Stockton



Madison



2-2 Piece Arched Madison



4 Piece Arched Madison


*Features window designs, not interchangeable inserts.

RESIDENTIAL DOOR FEATURES

All features are not available on all models.

For additional information, please see numbered footnotes on page 30.


GLAZING OPTIONS⁷.




*Caming is available in either: Brass  Platinum 

COLOR SELECTIONS⁹.

SOLID



FIBERGLASS



The color selections have been matched as closely as possible. Colors shown may vary due to reproduction and printing processes. Refer to samples at your local C.H.I. Overhead Doors Distributor for exact color match.

RESIDENTIAL DOOR FEATURES

APPEARANCE AND ENDURANCE PACKAGES

Appearance Package. All hardware (excluding torsion shafts, drums, springs and cables), track and struts are powder coated white. White 10 ball nylon rollers included.

Endurance Package. Includes everything in the Appearance Package above, plus 25,000 cycle springs and a Lifetime Warranty to original homeowner on all hardware and springs. The Endurance Package is only available in Models 2216, 2290 and 5216.



1. Track 2. Strut 3. Top fixture and white 10 ball nylon roller 4. Inside step plate/handle 5. Bottom fixture with white 10 ball nylon roller 6. End hinge with white 10 ball nylon roller 7. Lift handle



Wind can be unpredictable and destructive. This is why C.H.I. Windbreaker Series and iSeries doors are designed, tested, and built to the most rugged specifications. Wind chamber tested to ensure wind-load resistance, these extra-sturdy designs provide enhanced defense against the elements.

C.H.I. Overhead Doors developed the resilient Windbreaker Series garage doors to protect against high wind conditions. The super-resilient C.H.I. iSeries Impact Approved doors have strength designed to withstand direct collision of projectiles and other windborne debris at high speeds.



C.H.I. Overhead Doors is pleased to use DOW[®] insulation products in our urthane core garage doors.

LIMITED LIFETIME WARRANTY

SECTIONS. C.H.I. Overhead Doors, Inc. ("C.H.I.") warrants garage door sections against splitting; cracking and rusting through.

- Residential applications are covered for as long as the original purchaser/homeowner owns the building the doors were installed in except as noted below.
- Model 2200 and model 2201 are warranted for five (5) years.
- Series 5800, 5600, 5500 and 5300 carriage house doors are warranted for three (3) years.
 - Dark colors with a light reflectance value of less than 50% will void the warranty on series 5800, 5600, 5500, and 5300 doors except when using any color of Sherwin-Williams[®] VinylSafe[™] paint.
- Series 5400 and 5700 wood carriage house doors are warranted for one (1) year.
 - Series 5400 and 5700 doors must be field painted according to C.H.I. painting instructions prior to installation.
 - 2700 Series and Accent Series factory applied finishes are warranted against defects in material and workmanship for a period of three (3) years from the time of purchase.
- Doors used in commercial applications are warranted for ten (10) years unless the specific model has a warranty less than ten (10) years as noted.

OTHER COMPONENTS. C.H.I. warrants all hardware against defects in materials and workmanship, except springs as follows:

- Residential 25 gauge pan door hardware is warranted for three (3) years.
- Residential 24 gauge pan, sandwich, carriage house and fiberglass door hardware is warranted for six (6) years.
- Model 2200, 2201 and commercial door hardware is warranted for one (1) year.

SPRINGS. C.H.I. warrants springs used in residential applications against defects in materials and workmanship as follows:

- Three (3) years for doors up to eight (8) feet high.
- One (1) year for doors over eight (8) feet high and for models 2200 and 2201.

C.H.I. warrants springs used in commercial applications for one (1) year.

All warranty periods begin with the date of manufacture. C.H.I.'s obligations are strictly limited to repair or replacement of defective parts and components during the warranty period.

This limited warranty excludes: (1) rust caused by damages or scratching; (2) damage resulting from exposure to corrosive chemicals, corrosive fumes, salt environments including coastal areas, condensation, water or fire; (3) damages caused by accident, improper use, negligent operation, improper installation, improper maintenance or normal wear; (4) shipping, installation or labor charges; (5) defects in paints or coatings used to finish door sections; (6) any product or component which is modified, altered, or not part of the original door; (7) damages resulting from any circumstances beyond the direct control of C.H.I. and (8) minor expansion and contraction gaps in overlay material on carriage house and fiberglass doors.

In the event of a defective component, contact the dealer the door was purchased from within fifteen (15) days from discovery of the defect. C.H.I. reserves the right to inspect all products alleged to be defective and to verify eligibility of this limited warranty.

THIS LIMITED WARRANTY EXCLUDES ANY LOSS OR DAMAGE NOT SPECIFICALLY UNDERTAKEN HEREIN, INCLUDING, WITHOUT LIMITATION, ANY CONSEQUENTIAL OR INCIDENTAL DAMAGES, SUCH AS DEATH, INJURY, DAMAGES TO PROPERTY, OR DAMAGES ARISING FROM LOSS OF USE OF ANY PRODUCT OR FACILITY. ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND OF MERCHANTABILITY, ARE HEREBY EXPRESSLY EXCLUDED.

This warranty is non-transferable.

FOOTNOTES

- R-vlue testing is in accordance with ASTM C518 standards 2. Unfinished doors are for field gel staining only. Follow directions provided by gel stain manufacturer. If field painting is desired, the door must be factory finished (painted) prior to any painting in the field. Use only oil based or 100% acrylic water based paint when repainting doors. 3. Extra heavy paint system consists of .25 mil. primer with rust inhibitor and a .75 mil. coating of baked-on polyester paint. 4. Endurance and Appearance Packages are standard white, custom colors are available at an extra charge. 5. Available for models 2250-51-55, 4250-51-55, 5250-51, 5950-51, 5283, 5983, 5216, and 5916. 6. Accents is available for models 5216, 5283, 5916 and 5983 ONLY. 7. All designer lites are either transparent or semi-transparent. 8. All color options are not available for all models. Refer to samples at your local C.H.I. Overhead Doors Distributor for exact color match. 9. Available in long panel. 10. Chlorofluorocarbon (CFC) free.

All information presented is based on the specifications and features available at the time of printing and is subject to change without notice.